



ON-COUNTER VERTICAL PRESENTATION SCANNER

The Magellan 2200VS scanner is specifically designed for retailers that require high performance in a compact, vertical form factor. Tailored for very small counter retail checkout environments with medium to high volume point-of-sale (POS) transactions, the Magellan 2200VS scanner is particularly effective in drug stores, convenience stores, smaller to medium sized grocery stores, DIY stores and specialty stores. With category leading scanning performance for superior ergonomics and throughput, the 2200VS demonstrates the Magellan brand renowned quality and reliability.

SOFTWARE MANAGEMENT

Advanced software decoding algorithms provide the industry's best scanning speed and simultaneously improve first pass read rates of damaged, wrinkled, or poorly printed bar codes delivering improved operational efficiencies at the retail checkout.

Flash memory allows for easy software upgrades that help extend the life of the retailer's investment. In addition, an auxiliary RS-232 port can be utilized in a variety of ways, including adding a handheld scanner, programming and configuring the scanner, or accessing the scanner's label data output.



FEATURES

- World's leading vertical on-counter single plane presentation bar code scanner
- Renowned Magellan brand quality and reliability
- Best in class scanning performance for both sweep and presentation scanning styles
- FirstStrike advanced decoding software delivers the best performance in reading poor quality labels
- Flash memory for easy software upgrades in the field
- Multiple interface solution supports all popular host interfaces in every unit
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Checkpoint Systems and Sensormatic EAS compatible (Optional)
- Value Added Features:
 - Diagnostic Reporting - For improved preventative maintenance
 - Productivity Index Reporting™ - Helps identify poorly printed labels (Optional)
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Retail: Point of Sale

DECODING CAPABILITY

| | |
|-------------------|--|
| 1D / LINEAR CODES | Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes. |
| STACKED CODES | GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional |

ELECTRICAL

| | |
|-----------------------|---|
| AC POWER REQUIREMENTS | AC Input: 90-265 VAC, 47-63 Hz |
| POWER CONSUMPTION | Operating (Maximum): 9.6 Watts Operating (Nominal): 4.0 Watts Sleep Mode: 2.5 Watts |

ENVIRONMENTAL

| | |
|--------------------------------|--|
| ESD PROTECTION (AIR DISCHARGE) | 25 kV |
| HUMIDITY (NON-CONDENSING) | 5 - 95% |
| TEMPERATURE | Operating: 10 to 40 °C / 50 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F |

INTERFACES

| | |
|-----------------|--|
| INTERFACES | IBM 46xx; Keyboard Wedge; OEM (IBM) USB; RS-232; USB |
| AUXILIARY PORTS | Powered RS-232 |

OPTIONAL FEATURES

| | |
|----------------------|---|
| EAS FEATURES | Checkpoint Systems: Integrated EAS hardware will work with Counterpoint IX and Evolve D11 models; |
| VALUE ADDED FEATURES | Sensormatic: Good Read Acknowledgement Diagnostic Reporting; Productivity Index Reporting™ (PIR) |

PHYSICAL CHARACTERISTICS

| | |
|------------|---|
| DIMENSIONS | 15.2 x 15.2 x 9.7 cm / 6.0 x 6.0 x 3.8 in |
| WEIGHT | 1.1 kg / 2.5 lb |

READING PERFORMANCE

| | |
|--------------------|-------------------------------------|
| MOTOR SPEED | 6,000 rpm |
| READ HEIGHT | 15.2 cm / 6.0 in |
| READING INDICATORS | Beeper (Adjustable Tone and Volume) |
| SCAN LINES | 20 |

SAFETY & REGULATORY

| | |
|--------------------------|--|
| AGENCY APPROVALS | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. Complies to EU RoHS |
| ENVIRONMENTAL COMPLIANCE | Complies to EU RoHS |
| LASER CLASSIFICATION | Caution Laser Radiation - Do not stare into beam; CDRH Class IIa; EN 60825-1 Class 1 |

UTILITIES

| | |
|----------------|---|
| OPOS / JAVAPOS | JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at no charge. |
|----------------|---|

WARRANTY

| | |
|----------|-------------------------|
| WARRANTY | 3-Year Factory Warranty |
|----------|-------------------------|