



EXPERT SBC

Industrial PC - EXPERT 1700 SBC SXGA i-C T - stationary

[Industrial PC](#) » [stationary](#) » [EXPERT SBC](#) »

The different designs of the EXPERT series by FORSIS develop areas

in which feedback stations are necessary in the most extreme of usage conditions. Protection class IP65 is a necessary prerequisite here.

In addition to the impermeability of the devices, adherence to hygiene standards and optional application in extended temperature ranges are demanded.

To mention the sectors by name:

- Food-processing crafts
- Food industry
- Pharmaceutical manufacturers and the pharmaceutical industry

The features of the SBC series are:

- Plug exit in the rear
- Cable exit protected according to IP65
- Cable penetration without soldering work

Stainless steel housing

IP-class front IP69k, connections IP65

CPU i-Cel 1047UE 2x1,4 GHz, 4GB RAM, SSD 128GB MLC

17" LCD TFT, 1280x1024, resistive touchscreen

2x RS232, 2x USB 2.0, 2x USB 3.0, 2x GbE

DisplayPort, VGA, Mini PCIe fullsize / halfsize

Working temperature: -5°C to 45°C

Power supply: 230V AC, 60 VA, internal

Cable outlet: protected/ rear

Mounting: side / threaded holes

WxHxD:450x385x130 mm, 13 kg



Specification

Device specification		
material:	material	V2A / V4A
surface: outside,	outside	gebürstet
	inside	geschliffen
Weight	kg	13
dimensions WxHxD (mm):	AbB	450
	AbH	385
	Abi	130
Man-Machine-Interface		
LCD	Diagonal (")	17
	Resolution	SXGA
	Pixel	1280 x 1024
Touchscreen	Technology	analog resisitiv
PC-System specification		
CPU	Name	Intel® Celeron™ 1047UE
	# of Cores	2
	Frequency (GHz)	1,4
	Fan	●
RAM	Standard (GB)	4
	Maximum (GB)	8
Mass storage	SSD (GB)	128
	HDD (GB)	○
	CF (GB)	○
Interfaces externally		
Serial	RS232	2
	RS422/485	○
USB	USB 2.0	2
	USB 3.0	2
Monitor connections	DisplayPort	●
	HDMI	●
	DVI	-
	VGA	1
Ethernet	1000 Mbit/s	2
	100 Mbit/s	-
Mouse/Keyboard		-
Slots		
PCI104		-
ISA		-
PCI		-
Mini PCIe	Full size	1



	Half size	1
environmental conditions:		
temperatue range:	°C	-5°C bis 45°C
non-condensing humidity:	%	0-95
Approvals		CE
Power supply		
Input voltage	V	230
Input current	Kind	AC
Power consumption	W	60
Safety class		
Front	IP	69k
interface	IP	65
cable outlet		
protected		○
Cable strain relief,		○
lead downwards		rear side
assembly points:		
Mounting bracket set for desk and		●
Rear	VESA 100	-
operating Systems		
Windows	Windows CE	-
	Windows Embedded	○
	7	
	Windows Embedded	○
	8	
	Windows 10 IoT	-
	Windows 7	○
Windows 8	○	
Windows 10	-	
IGEL		-
extension		
Wireless	wireless	○
	Bluetooth	○
Mobile Web	UMTS/LTE	○
RFID		○
windshield		●
Sound		-
USV		-
heating		-



Gallery



expert-sbc-front.jpg



expert-sbc-interface-open.jpg



expert-sbc-interface-close.jpg

Schnittstellenabdeckung mit Kabelführung durch RITTAL Klemmtechnik.

Schutzklasse IP65.

Unterschiedliche Anzahl von Kabeldurchführungen möglich.



EXPERT-SBC-RFID.jpg



Expert-SBC-PG.jpg

Schnittstellenabdeckung mit PG-Verschraubungen



expert-desktop-mount.jpg

Standfuss zur Gerätemontage auf dem Tisch.

Unterschiedliche Ausführungen für EXPERT 1500 / 1700 und 1900.



Für weitere Informationen stehen wir gerne zur Verfügung

D	FORSIS GmbH	Schwanenstr. 5	88214	Ravensburg	T	+49	(0) 751 76414 363	info@forsis.de	www.forsis.de
		An der Straßenbahn 10	31157	Sarstedt / H	T		(0) 5066 90229 160		
CH	FORSIS Schweiz GmbH	Solothurnstr. 154	2504	Biel	T	+41	(0) 32 333 1073	info@forsis.ch	www.forsis.ch
A	FORSIS Österreich GmbH	Höchster Str. 24	6850	Dornbirn	T	+43	(0) 5572 3727 09	info@forsis.at	www.forsis.at
NL	RBK Automatisierung bv	Keulenstraat 18	7418	ET Deventer	T	+31	(0) 570 680 116	info@forsis-nl.nl	www.forsis-nl.nl
S	AceIQ AB	Stridsvagnsvägen	29139	Kristianstad	T	+46	(0) 763 18 42 18	info@aceiq.com	www.aceiq.com



Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhaltes ist nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlung verpflichtet zu Schadenersatz. Alle Rechte vorbehalten. Technische Änderungen sind möglich.

