

FORSIS

product information



PROFI S

Industrial PC - PROFIS 1900 SXGA i3 T - stationary

[Industrial PC](#) » [stationary](#) » [PROFI S](#) »

The PROFIS series is mainly designed for stationary use in industrial environments. Special focus was put on the creation of devices that can be consistently used for the different customer wishes. From simplest BDE feedback to the most complex visualisation.

The features of the PROFIS series are:
LCD versions up to 21.5" at format 16:9
MULTITOUCH function in 18.5" and 21.5" device designs
CPU support of I3 and I7

Metal housing IP-class front IP65, connections IP52
CPU Intel Core i3 3217UE, 4 GB RAM, SSD 128 GB MLC
19" LCD TFT, 1280x1024, resistive touchscreen
2x RS232, 2x USB 2.0, 2x USB 3.0, 2x GbE
DisplayPort, VGA, Mini PCIe fullsize / halfsize
Working temperature: 0°C to 50°C
Power supply: 230V AC, 60 VA, internal
Cable outlet: protected/ strain relieved | below
Attachment points: at the back / VESA 100
WxHxD: 435x412x115 mm, 11kg



Specification

Device specification		
material:	material	Steel sheet
surface: outside,	outside	powdered
	inside	galvanized
weight (kg):	weight with battery	11
dimensions WxHxD (mm):	AbB	435
	AbH	412
	Abi	115
Man-Machine-Interface		
"LCD diagonal (mm/"): "	LCD	19
resolution:	solution	SXGA
	Pixel	1280 x 1024
touch	touch	analog resisitiv
PC-System specification		
CPU Typ	cpu	Intel® Core™ i3 3217UE
FAN	fan	•
CORES	cores	2
Frequenz	Freq	1,6
RAM (GB)	rammax	8
	RAM	4
fixed memory		
HD (GB)	HDD	○
CF (GB)	CF	○
SSD (GB)	SSD	128
Interfaces externally		
RS232	RS232	2
RS422/485	RS422/485	○
USB	usb2	2
	usb3	2
VGA	vga	1
HDMI	hdmi	1
DisplayPort	DP	1
Ethernet GbE	ethernet GbE	2
Mouse/KB	mousekbd	-
Slots		
PCI104	PCI104	-
ISA	ISA	-
PCI	PCI	-



Mini PCIe	mini pcie full	1
	mini pcie half	1
environmental conditions:		
temperatue range:	temp	0-50
non-condensing humidity:	condens	0-95
Approvals	approv	CE
Power supply		
typical voltage IN:	uin	230
power consumption:	child	AC
	power	60
Safety class		
front	frontip	65
interface	interfaceip	52
cable outlet		
protected	protect cable	○
Cable strain relief,	cable train	○
lead downwards	cable lead	below
assembly points:		
Mounting bracket set for desk and wall installtion included in scope of delivery.	side	-
	back	●
operating Systems		
WINCE	WINCE	-
WES 7	Windows Embedded 7	○
WES 8	Windows Embedded 8	○
WIN 7	Windows 7	○
WIN 8	Windows 8	○
IGEL	IGEL	-
extension		
Sound	sound	○
RFID	RFID	○
WLAN	wireless	○
USV	UPS	-
windshield	glass	○
Bluetooth	Bluetooth	○
UMTS/LTE	UMTS/LTE	○
heating	heating	-



Gallery



PROFI-S-19-Front.jpg



PROFI-S-RFID.jpg



profi-cable-protect.jpg



profi-interface-close.jpg



profi-s-19-side.jpg

Für weitere Informationen stehen wir gerne zur Verfügung

D	FORSIS GmbH	Schwanenstr. 5	88214	Ravensburg	T	+49	(0) 751 76414 363	info@forsis.de	www.forsis.de
		An der Straßenbahn 10	31157	Sarstedt / H	T		(0) 5066 90229 160		
CH	FORSIS Schweiz GmbH	Solothurnstr. 154	2504	Biel	T	+41	(0) 32 333 1073	info@forsis.ch	www.forsis.ch
A	FORSIS Österreich GmbH	Höchster Str. 24	6850	Dornbirn	T	+43	(0) 5572 3727 09	info@forsis.at	www.forsis.at
NL	RBK Automatisierung bv	Keulenstraat 18	7418	ET Deventer	T	+31	(0) 570 680 116	info@forsis-nl.nl	www.forsis-nl.nl
S	AceIQ AB	Stridsvagnsvägen	29139	Kristianstad	T	+46	(0) 763 18 42 18	info@aceiq.com	www.aceiq.com



Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhaltes ist nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlung verpflichtet zu Schadenersatz. Alle Rechte vorbehalten. Technische Änderungen sind möglich.

