

## Product profile

# PB<sub>22/32/50</sub>

## Rugged Mobile Label Printers



- The industry's fastest 2, 3, and 4 inch rugged mobile label printers
- Built rugged to survive real-world industrial and retail environments
- Two to three times faster time-to-first-label than competitive products
- Low cost of development, deployment and support
- Seamless integration with Intermec mobile computers and other mobile devices
- Secure wired and wireless communications options: Bluetooth®, 802.11 b/g, USB, Serial
- Label sensors minimize printing errors and reduce waste
- SmartSystems® remote device management reduces support needs
- Optimized for Intermec media, including linerless label media options

The Intermec rugged mobile label printer family delivers the fastest choice for customers with demanding applications in warehousing, distribution, in-store retail and enterprise asset management. Coupled with Intermec rugged mobile computers and software, the PB22, PB32 and PB50 mobile label printers help companies improve productivity and efficiency while lowering the total cost of ownership.

With ultra-fast print speed and proven two to three times faster time-to-first-label\* than competitive products, these printers deliver measurable improvements in worker productivity and accuracy. Unique design elements, such as the label gap and label take sensors, help maintain productivity while reducing waste.

The PB label printer family is built on a common electrical and mechanical foundation, and integrates closely with Intermec mobile computers and software, including Intermec Terminal Emulation (ITE) and Intermec SmartSystems®. This integrated approach provides significant efficiencies in development, deployment and support, and optimizes speed and performance. Intermec SmartSystems provides remote monitoring and diagnostics to networked devices so problems can be resolved

quickly. Shared accessories across the family add flexibility and reduce spares inventory and costs. Intermec media options, designed specifically for the PB printers, ensure consistently high print quality across a range of applications.

Leveraging the Intermec platform gives companies a solution that can adapt and grow with their needs. As "smart" printers, the rugged PB printers can host stand-alone applications developed through Intermec Fingerprint programming to address custom requirements today or in the future, without the need to upgrade hardware.

The printers' comprehensive options and easy adaptability meet a range of application needs. Drop-in media loading, adjustable media holders, and the flexibility to print either receipts or labels enables workers to easily change tasks without changing equipment. A choice of secure wired and wireless interfaces (802.11 b/g, BT, Serial, USB) allows you to select the one that fits your environment. Multiple carrying options are available, including belt clip, shoulder strap and vehicle mount.

The rugged design of the PB22, PB32 and PB50 printers means performance you can depend on, day after day. Built

to thrive in the same environment as Intermec computers, the printers have a 5 foot multiple drop spec, IP54 seal rating, and forklift-strength shock and vibration specs, minimizing repairs and downtime. When issues do arise, Intermec Medallion Complete service contracts deliver peace-of-mind and insurance against unbudgeted repair costs.

#### Physical Characteristics

##### PB22:

**Width:** 101 mm (4 in)  
**Height:** 176 mm (6.9 in)  
**Depth:** 71 mm (2.8 in)  
**Weight (with battery):** 678 g (23.9oz)

##### PB32:

**Width:** 127 mm (5 in)  
**Height:** 182 mm (7.2 in)  
**Depth:** 81 mm (3.2 in)  
**Weight (with battery):** 828 g (29.2oz)

##### PB50:

**Width:** 160 mm (6.3 in)  
**Height:** 174.5 mm (6.9 in)  
**Depth:** 78.8 mm (3.1 in)  
**Weight (with battery):** 1189 g (42.0 oz)

#### Environment

**Operating temperature:** -15°C to 50°C (5°F to 122°F)  
**Storage temperature:** -30°C to 70°C (-22°F to 158°F)  
**Humidity:** 10 to 90% (non-condensing)  
**Sealing:** IP54 (excludes paper path)  
**Drop spec:** 1.5m (5 ft.) drops to concrete; 26 times including all corners and sides  
**PB22/32:** 2m (6.5 ft) multiple drops to concrete with optional protective case

#### Power

**PB22/32:** 7.4V Li-Ion, 2.3 Ah, rechargeable battery (typical)  
**PB50:** 14.8V Li-Ion, 2.2 Ah, rechargeable battery

#### Memory

**RAM:** 16MB  
**Flash:** 64MB

#### Standard Communications

RS-232 Serial  
USB v.2.0

#### Optional Communications

Bluetooth® (v2.0, Class 1)  
802.11b/g

#### Wireless Security

**Authentication & Encryption Options:** WEP (64 and 128 bit) LEAP; WPA-PSK (TKIP / RC4); WPA2/802.11i-PSK (CCMP / AES); EAP-TTLS, -PEAP, -FAST

#### Print Speed and Resolution

4ips (101.6mm/sec)  
203 dpi (8 dots/mm)

#### Print Technology

**Printhead:** Direct thermal

#### Media

**Type:** Labels or receipt media

##### Intermec Media:

**Labels and Tags:** Duratherm II, Duratherm III, Duratherm NIR, Duratherm III IR, Duratherm III Synthetic, Duratherm III Linerless, Duratherm II 5-mil Tag  
**Receipts:** Duratherm Receipt II, Duratherm Receipt III

##### Media Width Ranges:

**PB22:** 25.4mm to 55.88mm (1 to 2.2 in)  
**PB32:** 30.48mm to 83.82mm (1.2 to 3.3 in)  
**PB50:** 49mm to 111.5mm (2 to 4.39 in)

**Core ID:** 19mm (0.75 in) standard, 10.16 mm (0.4 in) supported

##### Max OD:

**PB22:** 57.2mm (2.25 in)  
**PB32:** 67.3mm (2.65 in)  
**PB50:** 67.3mm (2.65 in)

#### Software

##### Programming Languages:

IPL, Fingerprint, ZSim (ZPLII Simulation), ESC-P, DSim (DPL), CSim (CPCL)

##### Character Sets

**Standard:** English and Latin

**Optional:** Western European, ASCII, CodePage 850, Central European, Cyrillic, Latin, Greek, Turkish, Hebrew, Arabic, Baltic, Baltic RIM, Vietnamese, Thai, Simplified Chinese, Traditional Chinese, Korean, UTF-8

#### Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos.

#### Barcode Symbolologies

All major 1D and 2D symbolologies are supported.

#### User Interface

LCD and 4 buttons: standby, paper feed, setup, info  
Four audio status indicators: error alert, hardware change alert, button press alert and startup alert.

#### Accessories

Hand strap, shoulder strap, belt clip, protective case, cart mount, vehicle mount, battery pack, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable

#### Safety Approvals

**North America:** UL and cUL Listed, UL 60950-1

**Europe:** D Mark, EN 60950-1; CE marked

**Mexico:** NYCE Certified, NOM 19

**Other Countries:** IEC 60950-1

#### EMC Approvals

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN55022 Class B + EN55024); CISPR22

#### Warranty

One year; additional Medallion service packages available

#### North America

6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348 2600  
Fax: (425) 355 9551

#### North Latin America

Mexico  
Phone: (+52) 55 52 41 48 00  
Toll Free NOLA:  
01800 490 4990

#### South Latin America

Brazil  
Phone: (+55) 11 3711 6770  
Fax: (+55) 11 5502 6780

#### Europe, Middle East & Africa

Reading, United Kingdom  
Phone: (+44) 118 923 0800  
Fax: (+44) 118 923 0801

#### Asia Pacific

Singapore  
Phone: (+65) 6303 2100  
Fax: (+65) 6303 2199

#### Media Sales

EMEA: (+31) 24 372 3167  
USA: (513) 874 5882  
<http://intermec.custhelp.com>

#### Sales

Toll Free NA: (800) 934 3163  
Toll in NA: (425) 348 2726  
Freephone ROW:  
00800 4488 8844

#### OEM Sales

Phone: (425) 348 2762

#### Customer Service & Support

Toll Free NA: (800) 755 5505  
Toll in NA: (425) 356 1799  
EMEA: [intermec.custhelp.com](mailto:intermec.custhelp.com)

#### Internet

[www.intermec.com](http://www.intermec.com)

#### Worldwide Locations

[www.intermec.com/locations](http://www.intermec.com/locations)

