

MARK 2

● standard range



Smallest and lightest wearable scanner*



Scan range of 4 - 31 inch (10 - 80cm)



3 different wearables to choose from



up to 6000 scans



Optic, haptic and acoustic feedback function



Connection via Bluetooth Low Energy and 868/915 MHz

* MARK 2 standard range is shown here in original size (1.9x1.7 inch/50x45mm).

MARK 2 standard range



- ✓ Suitable for 1D and 2D barcode reading from shorter distances (*4 - 31 inch / 10 - 80 cm*)
- ✓ MARK 2 can be connected via Bluetooth Low Energy (BLE) or 868/915 MHz
- ✓ Haptic, acoustic and optic feedback function
- ✓ Battery life up to 6000 scans

USE OF MARK 2 standard range

- ✓ Pre- and post assembly
- ✓ Workstations (quality control, reworking, etc.)
- ✓ Material supply (kitting, presequencing, etc.)
- ✓ Packaging
- ✓ Picking (supermarket principle, small parts picking, etc.)

ACCESS POINT



- ✓ Transmission via 868/915 MHz, Channel selection is possible
- ✓ Connection via USB, HID, CDC or RS232
- ✓ Easy configuration and intergration at: config.proglove.de

CHARGING STATION



- ✓ Secure hold both for MARK 2 standard range, mid range and for MARK Basic
- ✓ Different mounting types are possible (wall mounting, mounting with cables, etc.)

MARK 2 standard range

AVAILABLE NOW

Please contact us for more information:

✉ sales@proglove.com
🌐 www.proglove.com

