

Looking for a rugged and reliable tablet with endless possibilities? The Unitech TB85 is designed to meet those needs!

## Scalability at its finest

Unitech proudly introduces the new standard in rugged, enterprise level tablets. Our TB85 features a durable design, combined with a strong interior and multiple additional extras. Our TB85 is equipped with a 14-pin POGO connection on the back for modules such as scanning or any other bespoke module. A scanning module can be easily connected to make the TB85 an even more complete device.

## Strong on the inside

The TB85 does not only feature a sturdy outside design, the inside of our new tablet is also quite impressive. Featuring the latest Android 8.0, GMS certified, combined with a 2.2 Ghz Octa-core processor, no task is to serious for the TB85.

With 32GB of internal storage and 4 GB of DDR3 memory, you can be assured that there will always be some space left available for you to save your latest work.

#### Stay connected

The combined strength of a rugged exterior with a superior interior is complimented by excellent connectivity. Equipped with NFC compatibility (frequency 13.56 Mhz at 0 ~ 3 cm),

WiFi 802.11 a/b/g/n/ac connection and 4G/LTE you are always connected and available. Next to this, the TB85 comes with Bluetooth 4.1 to communicate with other Unitech devices such as our RP100 RFID reader and MS652 ring scanner.

The TB85 features an 8" LCD touch screen with the ability to work while wearing gloves and is wet resistant. Also, the TB85 is extra durable thanks to its 8200 mAh chargeable battery which, if power runs out, is changeable as well. And even with battery, the device only weighs 650 grams, including the battery. This way, your business never has to wait.

#### **Features**

- Android 8.0 GMS with Octa-core CPU.
- POGO Pin extension with QC3.0 (Quick-charging).
- 14-pin POGO extension for modules.
- 8200 mAh changeable Li-ION battery.
- 32 GB eMMC + 4 GB DDR3 memory.
- 4G/LTE, WLAN 80211 a/b/g/n/ac, BT 4.1 and NFC.
- 8" display with Gorilla Glass 3 and GFF touch panel.
- IP67 rated with 1.2 meter to marble drop spec.





# v1 TB85 Specifications

Basic characteristics

Dimensions 241.92 x 151.99 x 17.76 mm Weight 630 g (including battery)

Battery 8200 mAh rechargeble Li-ion battery

POGO Pin extention, quick charge QC3.0

Operation System

CPU Qualcomm MSM8953 PRO
Octa core 2.2GHz Processor

Memory 32GB eMMC+4GB DDR3
OS Android 8.0 GMS certified

Display

8 inch display, 1280 x 800 Sunlight Readable

Touch panel GFF, Corilla Glass 3, Support glove operation\*

\*Depending on actual material & thickness

Keypad

8 function keys Power key, volume up, volume down,

return key, home key, menu key,

2\* custom keys

Keypad light Support

### Interface for module



Camera

Rear 13 mp with auto focus

Font 5 mp
Flash lights Double lights

Communication

SD 1x Micro SD SIM 1x Nano SIM

Sensors Ambinent light sensor with 1R

Hall sensor support for accessory

Acceleration sensor

Atmosphere pressure sensor

**Unitech Europe** 

Tilburg, The Netherlands

- Tel.: +31 (0)13 460 9292
- Email: info@eu.ute.com
- Website: eu.ute.com



GPS/Beidou Compass support, Embedded antenna,

Supports external antenna as well

RFID (NFC) Frequency 13.56MHz 0~3cm

WLAN WiFi/BT and NFC WiFi 802.11 a/b/g/n/ac Bluetooth Bluetooth 4.1

**WWAN** 

GSM 850 / 900 / 1800 / 1900

TD-SCDMA B34, 39 WCDMA B1, 2, 5, 8 CDMA/EVDO BC0

LTE-TDD B38, 39, 40, 41

LTE-FDD B1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 25, 28

CA

UL Intra-C Band 39, 40, 41
DL Intra-C Band 3, 39, 40, 41
DL Inter Band 1+3, Band 39+41

Audio

Audio PA
Audio Jack

High sound quality audio PA
3.5 mm earphone jack

Power Source

RTC-battery

Charging time Fully chareged less than 4 hours

Battery Approvals

UN 38.3, MSDS, IEC 62133, UL

Environmental

Operating temperature -20°C to 60 °C Storage temperature -40°C to 70 °C

Relative Humidity 5% ~ 95% (non-condensing)

EDS contact discharge 6KV,

air discharge 8KV

Drop Specification 1.2 m to marble

Ingress protection IP67

Software

Airwatch, SOTI, MoboLink, 12 Solutions

Safety and Warranty

One year warranty

CE/RED MIL-STD-810G

RoHS GMS



Unitech America Unitech Asia Pacific

Unitech China Unitech Europe

Unitech Japan

Unitech Taiwan

<sup>\*</sup> Warranty: Unitech reserves the right to call back the defect units at her discrete sole decision if Unitech may find it necessarily. Upon the calling, the returning shipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop the warranty coverage before expiration if the defect is found due to abused, sabotage, and/or caused by the acts of God Specifications subject to change without notice.