

Durable, multipurpose RFID reading

Looking for a durable solution for quick scanning and tagging inventory? The Unitech RP100 is a great new add-on for EA500PLUS.

Empowering EA500PLUS for RFID/UHF application

Much inventory and stock these days is being tagged with RFID. This radio-frequency identification uses electromagnetic fields to automatically identify and track tags. This makes checking stock a lot easier instead of counting piece by piece or box by box. The RP100 comes with a holder which is specifically designed for EA500PLUS. You only need to slide the EA500PLUS in the holder and close it. Your EA500PLUS is then ready for both barcode and RFID/UHF reading. Isn't it so easy?

Warehousing/In-store inventorying at its best

RFID is becoming a widely used technique for fast and efficient warehousing and in-store inventorying. Our RP100 is designed to meet these needs. Picking large orders and checking large inventory from near to far is an easy effort thanks to the RP100 integration with our EA500PLUS devices. The gun grip makes for easy and portable use and the wide range in RFID frequencies make this a widely applicable device.

Portability and durability

The gun grip with battery included weighs in at only 420 grams. The grip is made of durable material that withstands a drop up

to 1.5 meters onto a steel plate and can work in hot and cold environments. The scanner is able to do both 1D and 2D scanners and the RFID reader can read EU frequencies ranging from 865 to 868 Mhz. The RP100 can do up to 600 tags per second. It also features micro-USB to communicate flawlessly with the EA500PLUS or any other scanning device with Bluetooth 4.1.

The 5200 mAh battery included in the gun grip will extend working times, this way you get longer usage. You can charge the RP100 and EA500PLUS at the same time over the charging and communication cradle or the USB Type-C that is included in the box.

Features

- Optional 1D and 2D scanning capabilities.
- Reading up to 5 meters away.
- Standard with Circular antenna design or optional directive antenna.
- Up to 600 tags per second.
- Adjustable antenna output power for near to far reading.
- Rich set of SDK empowers APP to control the device and make it greatly usable.
- 5200 mAh rechargeable Li-ION battery.





- Operation System

CPU ARM7 Core

■ Data Capture

Barcode (optional) 1D or 2D Imager Barcode Scanner

RFID (UHF) 902 - 928 Mhz (US)

865 - 868 Mhz (EU)

916 - 921 Mhz (Japan 1W LBT) 916 - 923 Mhz (Japan 0.25W LBT)

Tag Reading Speed Up to 600 tags per second

0m - 5m Reading range

Protocol GEN2, ISO/IEC 18000-6

Audio

Buzzer

Environmental

Operating temperature -20°C to 60°C Storage temperature -30°C to 70°C Charging temperature 0°C to 45°C

Relative Humidity 5% ~ 95% (non-condensing)

Drop Specification 1.5m to steel plate

Sealing **IP65**

Power Source

Main battery 3.5V 5200mAh 19.24Wh Li-ION battery

Input DC 5V 2A

Yes Rechargeable

USB Type-C, VCP, HID Standard I/O Port

- Enclosure

Weight 420g (including battery)

76.1 mm x 173.7 mm x 139.8 mm Dimension (without holder for EA500/502/

EA500PLUS)

Gun Handle

Gun Handle with Battery Li-ION 3.7V, 5200mAh, Rechargeable

Communication

QUAD LOCK Mount Mechanism Mount (optional)

USB Type-C

Bluetooth 4.1 Class1 (HID, SPP, BLE) Bluetooth

RFID Module

RFID module with Impinj R2000

Additional Features

LED x 3, Buzzer and Vibrator

Certifications

CE & RED cerfified RoHS

Warranty

Device 1 year Battery 3 months

Accessoires

Standard Interface Cradle, Charge Only, USB Type-C USB Type-C Cable Hand Strap Gungrip





Unitech Europe

Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292

- Email: info@eu.ute.com
- Website: eu.ute.com









Unitech America Unitech Asia Pacific Unitech China Unitech Japan

^{*} Warranty: Unitech reserves the right to call back the defect units at her discrete sole decision if Unitech may find it necessarily. Upon the calling, the returning shipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop the warranty coverage before expiration if the defect is found due to abused, sabotage, and/or caused by the acts of God Specifications subject to change without notice.